



# Blueprint for 2000-04 Regional Haze Data Certification

IMPROVE Steering Committee Meeting

July 27, 2005

# Blueprint for 2000-04 Regional Haze Data Certification – Proposed Schedule

## ◆ August 2005

- UCD - complete preliminary data processing
- UCD/CIRA – assess and identify specific additional objective data criteria

## ◆ September 2005

- UCD (9/1/05?) - deliver preliminary data to CIRA
- UCD/DRI – suggest which specific additional objective criteria can be applied to preliminary data
- CIRA - post preliminary data on IMPROVE/VIEWS for initial haze planning review

## ◆ October through late 2005

- ?Whom? – complete Class I area-by-area evaluation, and provide “final” site-by-site data to CIRA
- CIRA – Post “final” 2000-04 baseline data on IMPROVE/VIEWS websites

# Blueprint for 2000-04 Regional Haze Data Certification – Bext Reporting Method

- ◆ Determine Bext reporting method for “final” regulatory planning dataset by site, using additional objective criteria
  - Use existing IMPROVE Bext reporting method for valid samples
  - Consider modifying Regional Haze Tracking Guidance to use modified Bext reporting method for uncertain samples by:
    - ◆ Reporting PM10 soil Bext, not FS and CM separately
    - ◆ Determining whether EC and OC can be reported separately, or as TC
    - ◆ Addressing NH4NO3 vs. Calcium and Sodium NO3
- ◆ Objectives of this exercise
  - Better?! than substituting other “average” monitored values
  - Final QA check for setting baseline value at each site
  - Recognize limits of what is “known” about visibility effects of measured mass for regional haze plans, especially for fire and dust impacts
  - Does not remove any data from IMPROVE database, but qualifies the data for use in first round of regional haze plans

# Blueprint for 2000-04 Regional Haze Data Certification

## – Ideas for Additional Objective Data Criteria

### ◆ Flow rate criteria

- Apply by sample period and by module from which IMPROVE Bext species are derived (SO<sub>4</sub>, NO<sub>3</sub>, EC, OC, FS, CM)
- Difference from design flow rate at actual atmospheric conditions from sample period is data quality metric
- Sample flow rate within  $\pm 10\%$ ?! = valid data, accept reporting of standard IMPROVE species Bext
- Sample flow rate more than  $\pm 10$  up to  $\pm 20\%$ ?! = uncertain data, action is to move to modified Bext reporting method (previous slide)
- Flow rate more than  $20\%$ ?! = sample data from that channel invalid, action is determine if modified Bext reporting method is appropriate or applicable

# Blueprint for 2000-04 Regional Haze Data Certification

## – Ideas for Additional Objective Data Criteria, cont.

- ◆ Laboratory analysis criteria - after applying flow rate criteria by sample period and by module from which IMPROVE Bext species are derived (SO<sub>4</sub>, NO<sub>3</sub>, EC, OC, FS, CM), then assess:
  - Module C OC<sub>p</sub> issue – analysis and recommendation for criteria for valid/invalid (if needed) and when to go to modified Total Carbon Bext method (previous slide)
  - Module A/B composition match issue[s] – analysis by monitor site (address SO<sub>4</sub> & NO<sub>3</sub> Bext method case-by-case)
  - Module A/D mass sampling issue – (only at masked sites? and/or poor flow control?) – use flow rate criteria (previous slide) to determine appropriate Bext reporting method (PM<sub>10</sub> Bext or FS/CM Bext values)
  - Other QA issues as noted by Nicole/Chuck/Warren/Ann (keep Titanium in fine soil Bext equation? etc.) – address site-by-site